


**Lateral Turning Low Air Loss Pump & Mattress System ATM931-985**

PUMP SPECIFICATION		MATTRESS SPECIFICATION	
Power:	90V / 50Hz, 240V / 60Hz	Cell Depth:	11" Inflated
Pressure Range:	8 - 36mmHg	Air Cell:	20 Alternating Air Cell
Air Volume Output:	1275 liters	Air Loss:	High Volume
Turning Cycle:	10, 20, 30, 60mins. (50Hz & 60 Hz)	Top Cover:	Removable & Washable
Power Cord:	Hospital Grade Cord & Plug	Foam Base:	2" eggshell foam
Power Cord Length:	14 foot	Air Tube Covering:	Yes
Firmness Adjustment:	Yes	CPR Deflation:	Yes
CPC Connectors:	Yes	CPC Connector:	Yes
Dimension:	14 x 11 x 6	Inflated Dimension:	11 x (42,48,54,60) x 80
Weight:	9 lbs	Weight:	23lbs, 25 lbs, 27 lbs or 29 lbs
Agency Approval:	UL, CSA		

- Specially designed for supporting large patients.
- Controls pressure, moisture, shear and friction, for prevention and treatment of stages I-IV Pressure sore ulcer.
- Use as a replacement of a standard mattress .
- Vapor permeable top cover which is machine washable.
- Buckle down top cover for easy removal.
- Fast filling blower based air controller unit.
- Reliable air controller unit provides hours of trouble free operation.
- Comes in width of 36", 42", 48", 54" or 60".
- Weight limit: 1000 lbs.
- HCPCS Code: E0277

**Bariatric**



The mattress' turning programmed allows the patient to regularly change position, thus varying the pressure applied to the different areas of the body.



**Key air controller feature includes:**

- Turning option: left, right, both or none.
- Turning angle: full, 3/4, 1/2, or 1/4 turns.
- Turning cycle time: 10, 20, 30, or 60 mins.
- Soft to firm adjustments.
- Max air flow for quick pump up of air cell.
- Power failure alarm.
- Electronic function lock button.